



DIGITAL INSULATION TESTER DIT99A

APPLICATION: This is a high Quality Multirange Insulation Tester. It's easy to Operate

FEATURES:

Max reading: 1999 counts

Measuring Range: On 250V, 500V, 1000V

Auto data hold

• Low Battery Indication

• Overload Indication: LCD displays "1"

Fault protection

buzzer alarms if short circuit

• Operation Environment: Temperature: 0℃ -

40°C; Humidity:30% -80% RH

Storage Environment: Temperature: -10℃ - 50℃;

Humidity <85%RH

• Powered Supply: 8 X AA Size batteries.

• Display: 54 x 26mm.

Dimension: 140 x 100 x 48 mmWeight: 500g including Batteries

Accessories: Instructional manual, 8 Nos. 1.5V Batteries, Test Leads.



SPECIFICATION:

Voltage	Range	Measurement	Resolution	Medium	Accuracy
		Range		Resistance	
250V	200ΜΩ	2ΜΩ~200ΜΩ	0.1ΜΩ	2ΜΩ	±(5%+5digits)
500V	1000ΜΩ	20ΜΩ~1000ΜΩ	1ΜΩ	20ΜΩ	±(4%+5digits)
1000V	2000 ΜΩ	20ΜΩ~2000ΜΩ	1ΜΩ	20ΜΩ	±(5%+5digits)