



## **DIGITAL INSULATION TESTER DIT2520**

**APPLICATION:** The meter with auto range selection is digital Insulating resistance tester & Digital multimeter. It has features of complete functions, high accuracy, reliability in operation.

## **FEATURES:**

- Display 3 ¾ Digits 4000 Counts, Jumbo LCD display & backlight.
- · Data hold.
- Overload Indication "OL".
- · Low battery Indication.
- Operating environment 0° to 40°C < 75% RH ☐ Storage environment -10° to 60°C < 80% RH ☐ Sampling rate 2 times/sec.</li>
- Power off: 1) Manual off 2) Auto Power Off
- The meter will turn off after 15 minutes (approx.) from last key operation.
- Battery: 1.5V x 6, AA size.
- Display Size: 61 X 51 mm
- Dimension & weight: 170 x 156 x 64mm, ☐ Weight: 650g including the batteries.
- Accessories: 3 pcs Leads, 6pcs 1.5 V AA Batteries, 3pcs clips, Instruction manual, carrying case & gift box.



## **SPECIFICATION:**

Rated Voltage	Measurement range	Accuracy
500V	0.5ΜΩ-4GΩ	±3%rdg±5
1000V	1.5ΜΩ-4GΩ	±5%rdg±5
2500V	5ΜΩ-40GΩ	±10%rdg±5

## **DIGITAL MULTIMETER**

DCV: 0.0mv to 1000V,  $\pm$  0.8% ACV: 0.0mv to 700V,  $\pm$  1.0% DCA :0.0mA to 400ma,  $\pm$  0.8% ACA: 0.0mA to 400ma,  $\pm$  1.0% Resistance: 0 $\Omega$  to 40 M $\Omega$ ,  $\pm$  2%

CAP:  $0\mu F$  to  $40\mu F$ ,  $\pm 3\%$ 

Frequency: 0Hz to 4 MHz, ± 0.5%

**Diode & Continuity**