

SOUND LEVEL METER SL4012

APPLICATION: Applicable to measure the Sound level of environment, Machinery, Vehicles, Ships & Other Noise.

FEATURES:

- Display: 14mm (0.55") LCD Display with Backlight.
- Meter Permits the option of "A", "C" & "Flat(F)" Weighting
- Response Type: Slow, fast Built in calibration Signal (94DB) Low Battery Indication.
- Auto/Manual Power Off.
- 1/2 inch Electrets Condenser Type Microphone Sensor.
- Memory: 30Readings.
- PC Interface: RS232 Cable & Software.
- Alarm Function (Settable)
- Power Supply: 1.5 Volt *4pcs AAA Size Batteries.
- Display Size: 49 X 28 mm.
- Unit Size : 225 X 63 X 26 mm.
- Weight : 170 gm (Including Batteries)
- Accessories: Instruction Manual, carrying Case, Wind screen
Optional Accessories: ND9 Calibrator, RS232 Cable & Software.



SPECIFICATION:

BASIC FUNCTION	RANGE
Measuring Parameter:	LP, L max, Leq, LN.
Measurement range	LP :30~130dB (A) 35~130dB (C, F) Leq:30-130dB LN: 0~100%
Resolution	0.1 dB
Accuracy	±1dB