

PARTICLE COUNTER



This 4 in 1 Particle Counter comes with 2.8" colour TFT LCD display & a Micro SD memory card for capturing images (JPEG) or video (3GP) for viewing on your PC. Proving fast, easy and accurate readings for particle counter, GAS (HCHO, CO) detectors (Model DT-9881 only), air temperature & relative humidity, most surface temperature measurements.

It is the first combination of these measurements in world. Would be the best instrument for environment protection and energy conservation. The dew-point temperature measurement will be very visible for wet and dry proof. It is a good handy industrial measurement and data analyser. The real scene and time can be displayed on colour TFT LCD. Any memory readings can be recorded in Micro SD card. Offline analysis of the measured air quality under the support of software, can be done.



- 2.8" TFT 320*240 pixels Color LCD display
- Images (JPEG) & Video (3GP)
- Simultaneously measure and display 6 channel of particle sizes, measure particle size down to 0.3 µm
- Micro-SD (max. 8GB) memory card, USB interface.
- Air temperature and humidity, Dew-Point & Wet Bulb temperature
- MAX, MIN, DIF, AVG record, Date/time setup controls, Alarm
- Auto Power Off
- Selectable sample time, count data, programmable delay.
- Store 5000 records of date, time, counts, relative humidity, temperature, sample volumes, alarms and location label.

SPECIFICATION:

Channels	0.3, 0.5, 1.0, 2.5, 5.0, 10µm
Flow Rate	0.1ft ³ (2.83L/min)
Counting Efficiency	50% @ 0.3 µm; 100 % for particles > 0.45 µm
Coincidence Loss	5% at 2,000,000 particles per ft ³
Data Storage	5000 sample records (Micro-SD card)

Count Modes	Cumulative, Differential, Concentration,
Display resolution	0.01ppm

Air Temperature and Relative Humidity Measurement

Air Temperature Range	0°C to 50°C (32°F to 122°F)
Dew-point Temperature Range	0°C to 50°C (32°F to 122°F)
Relative Humidity Range	0 to 100%RH
Air temperature Accuracy	±0.5°C (0.9°F) 10°C to 40°C
	±1.0°C (1.8°F) others
Dew-point temp. Accuracy	±0.5°C (0.9°F) 10°C to 40°C
	±1.0°C (1.8°F) others
Relative Hum. Accuracy	±3%RH 40% to 60%
	±3.5%RH 20% to 40% and 60% to 80%
	±5%RH 0% to 20% and 80% to 100%
Operating Temperature	0°C to 50°C (32°F to 122°F)
Storage Temperature	-10°C to 60°C (14°F to 140°F)
Relative Humidity	10 to 90%RH non-condensing
Display	2.8" 320*240 Color LCD with backlight
Power	
Battery	Rechargeable battery
Battery Life	About 4 hours continuous use
Battery Charge Time	About 2 hours with AC adapter

ACCESSORIES:

Battery, Gift Box, Carrying Case and Instruction Manual

One year warranty against Any Manufacturing Defects.