

INTRODUCTION

DT-1350 Digital clamp meter has a 3-1/2 digit 2000 Count LCD display and is powered by two AAA Batteries. The Unit adopts full function overload protection circuit and can be used for the measurement of AC/DC voltage, AC current, DC current, Resistance, Diode and Continuity. It has a sturdy built and adopts a rotary switch that integrates Power on/off, Function selection and Range selection. It is handy and portable making it the ideal tool for electrical measurement.

SAFETY

The DT-1350 is in compliance with safety standards, including IEC61010-1, IEC 61010-2-032, CAT-III 600V and Pollution Degree II. Always read the manual carefully before using the device.

FEATURES

Display : 3 ½ Digit 2000 count LCD, with auto polarity conversion

Over Range Indication : OL will be shown on the LCD

Hold : Data hold on

Low Battery Indication : “” will be displayed on screen

AC Voltage : 200/750V

DC Voltage : 200mV / 2V / 20V / 200V / 1000V

AC Current : 200A / 1000A

DC Current : 200A / 1000A

Resistance : 200Ω / 2kΩ / 20kΩ / 200kΩ / 2MΩ /

Diode and Continuity test

Jaw Opening : Approx. 40mm

Overload Protection

CE CAT III 600V

Dimension : 250(L) × 97(W) × 48(H) mm

Weight : 345gm approx.(including battery)

Power Supply : 3V (2pcs AAA Batteries)

Working Environment : 0~40°C, 45% ~ 70% RH Non Condensing (When temperature is less than 10°C)

Storage Environment : -10°C~50°C, RH is less than 80%

Accessories : User Manual, Test Leads, 2pcs battery, Soft carry case



SPECIFICATIONS

AC Current Measurement

Range	Accuracy	Resolution
200A	±(3.0% + 8 digits)	0.1A
1000A		1A

Frequency Response : 50Hz/60Hz

Display : RMS of a Sine Wave; Average value responding

Overload Protection : 1200A (Input duration Max. 60 Seconds)

DC Current Measurement

Range	Accuracy	Resolution
200A	±(3.0% + 8 digits)	0.1A
1000A		1A

Overload Protection : 1200A (Input duration Max. 60 Seconds)

AC Voltage Measurement

Range	Accuracy	Resolution
200V	±(1.5% + 5 digits)	0.1V
750V		1V

Frequency Response : 50Hz/400Hz

Input Resistance : 10MΩ

Overload Protection : DC 1000V / AC 750V

DC Voltage Measurement

Range	Accuracy	Resolution
200mV	±(0.8% + 5 digits)	0.1mV
2V		0.001V
20V		0.01V
200V		0.1V
1000V		1V

Input Resistance : 10MΩ

Overload Protection : DC 1000V / AC 750V

Resistance Measurement

Range	Accuracy	Resolution
200Ω	±(1.5% + 5 digits)	0.1Ω
2kΩ		1Ω
20kΩ	±(1.5% + 3 digits)	0.01kΩ
200kΩ		0.1kΩ
2MΩ	±(2.0% + 5 digits)	1kΩ

Open circuit voltage : Less than 0.5V

Overload Protection : 500V DC/AC

Diode Measurement

Range	Resolution	Remark
	1mV	Forward voltage drop is about 2.8V

Continuity Test: Test using range when the resistance under test is less than 100Ω, the buzzer will sound.

Maximum Features
Pocket-friendly Price
