


FEATURES

- High resolution to 100µ AAC
- 3-1/2 digit (1999count) LCD display
- White LED backlight
- Auto power off
- 1.2" Jaw opening
- Max Hold: To record max Data
- Data Hold: To Freege displayed Data

GENERAL SPECIFICATIONS

Display	3-1/2 (1999 count) Digit LCD with white LED backlight
Overload indication	"OL" displayed on the LCD
Display rate	2 readings/second, nominal
Battery	Two "1.5V" batteries
Low Battery indication	"  "displayed on the LCD
Auto OFF	approx. 15 minutes
Operating conditions	32°F to 86°F (0°C to 30°C) 90% RH; 86°F to 104°F (30°C to 40°C) 75% RH; 104°F to 122°F (40°C to 50°C) 45% RH
Storage conditions	- 14°F to 140°F (-25°C to 60°C); < 90% Relative Humidity
Altitude	Operate at less than 3000 meters
Weight	225g (including batteries)
Dimensions	182 x 61 x 34mm (H X W X D)
Jaw opening	1.2"
Standards	EN61010-1, EN61010-2-032 Category II 600V,



Ranges

Function	Range	Resolution	Accuracy
AC Current (60Hz)	200mA	100µA	± (5.0% of reading + 8 digits)
	2A	1mA	± (5.0% of reading + 10 digits)
	200A	100mA	± (2.5% of reading + 10 digits)

*Technical Specifications & Appearance are subject to change without prior notice