

Digital TRMS AC/DC Leakage Current Clamp PRO 2010

FEATURES

- 0.1 mA current resolution
- True RMS measurement for all
- Backlit display
- LED Flashlight
- MAX MIN function
- Data Hold
- Zero Function
- Auto power-off
- Auto-ranging

SPECIFICATIONS

- Numerical Display: Backlit LCD, maximum reading 5000
- Low Battery Indication
- Sampling Rate: 2 times/sec
- Power Source: 1.5V size AAA battery x 2
- Auto Power-off: 30 minutes
- Safety Standards: CE, IEC-61010, CATIII 600V, UK CA
- Operating temperature: 0°C to 40°C (32°F to 104°F), < 80%RH
- Storage Temperature and Humidity: -10 C to 60 C (14°F to 140°F), < 80%RH
- Jaw Opening Diameter: 23mm
- Dimensions/ Weight: 207(L)x76(W)x34.5(H)mm / Approx. 281gms
- Accessories: Carrying Case, Batteries, Test Leads, User Manual



Function	Range	Resolution	Accuracy
DC Current	300.0mA/ 3000mA/ 10.00A	0.1mA/ 1mA/ 0.01A	±1%rdg ±10dgts
AC Current	300.0mA/ 3000mA/ 20.00A	0.1mA/ 1mA/ 0.01A	±1%rdg ±5dgts
DC Voltage	60V/ 600V	0.01V/ 0.1V	±1%rdg ±2dgts
AC Voltage	60V/ 600V	0.01V/ 0.1V	±1%rdg ±5dgts
Resistance	600/ 6K/ 60K/ 600KΩ	0.1Ω/ 1Ω/ 10Ω/ 100Ω	±1%rdg ±2dgts
⦿))	< 100Ω		

*The specifications and other information in this catalogue are subject to change without prior notice.