

Digital Contact & Non-Contact Combined Tachometer

NCTM-3000

FEATURES

- The Digital Tachometer provides fast and accurate Contact and Non-Contact RPM and surface speed measurements of rotating objects
- Measurement Type : Rotation Speed (RPM, rPm), Total Revolutions (REV), Frequency (HZ), Surface Speed (M/M,1/M, F/M, Y/M) and Length (Mts, In, Ft, Yd)
- Wide measuring range and high resolution
- High visibility digital LCD and Backlit Display
- 40 Reading Memories : 10 selectable MAX measurements, 10 selectable MIN measurements, 10 selectable AVG measurements, 10 selectable DATA measurements
- Laser sighting

SPECIFICATIONS

Display	: 5 digits LCD display
Accuracy	: ±0.05% or ±1RPM
Contact Test Range	: 2 to 20,000 RPM
Non-Contact Test Range	: 2 to 200,000 RPM
Tot Test Range	: 1 to 200,000 RPM
Resolution	: 0.001 to 1
Detecting Distance	: Up to 12 feet (50mm to 2500mm)
Time Base	: Quartz Crystal
Power Consumption	: Approx 45mA
Battery	: 9V or 6V AC adapter
Operating Temperature	: 0°C to 50°C (32°F to 122°F)
Size (HxWxD) Weight	: 160mm x 60mm x 42mm : 160g

Package includes:

Tachometer User Manual Carrying Case Laser Extension Head 3 Strips Reflective Tape Screw Adaptor Cone Adaptor RPM Sensor Tip Surface Speed Wheel 9V Battery



Setting Trends. Showing the Way.

www.metravi.com

METRAVI° NCTM-3000 TACHOMETER

*Technical Specifications & Appearance are subjet to change without prior notice