

**SPECIFICATIONS & DIMENSIONS**

<b>Display</b>	3 1/2 Digit 7 Segment Red colour LED 0.5" ht
<b>Cold Junction Compensation</b>	Automatic For T/C
<b>Sensor Input</b>	J, K, R, S, T/C PT-100 RTD 0.2%, mV, V, mA 0.1% (any one)
<b>Sensor open Indication</b>	By '1' at MSD
<b>Set Point</b>	Multiturn Trimpot for each set point
<b>Hyst Pot</b>	1 to 10°C for each set point for ON-OFF Model
<b>Tune Pot</b>	± 5 °C for each set point for Time Proportional Model
<b>Control Action</b>	ON/OFF or Time Proportional
<b>Control Output</b>	6 Amp or 20 Amp. 1 c/o Relay, 230 V.AC. 12V. DC, pulse o/p for S.S.R., for each set point
<b>Operating Temperature</b>	0-50°C (RH<80%)
<b>Supply</b>	230 V. AC. ¼ 10% 50 Hz

Dimensions (H x W x D)	96 X 96 120 MM	72 X 72 110 MM
Panel Cutout (h X w)	92 X 92 MM	68 X 68 MM



\*Technical Specifications & Appearance are subject to change without prior notice