



### FEATURES :

- 3½ DIGIT MULTIMETER
- 1,999 COUNT
- MAX / MIN MODE WITH DATA HOLD
- hFE TEST
- AUTO POWER OFF
- TRUE RMS
- NCV

### DC VOLTAGE

RANGE	RESOLUTION	ACCURACY
200mV	0.1 mV	±0.5% of rdg ±4 digits
2V	1mV	
20V	10mV	
200V	100mV	
1000V	1V	±1.0% of rdg ±4 digits

### DC CURRENT

RANGE	RESOLUTION	ACCURACY
200µA	0.01µA	±1.0% of rdg±5 digits
2000µA	1µA	
20mA	10µA	
200mA	100µA	
2A	1mA	
10A	10mA	±2.0% of rdg±10 digits

### TRANSISTOR hFE TEST (0-1000)

RANGE	TEST RANGE	TEST CURRENT / VOLTAGE
NPN & PNP	0~1000	Base current is approximate 15µA Vce about 1.2V

### AC VOLTAGE

RANGE	RESOLUTION	ACCURACY
2V	1mV	±0.8% of rdg ±6 digits
20V	10mV	
200V	100mV	
750V	1V	±1.0% of rdg ±6 digits

### AC CURRENT

RANGE	RESOLUTION	ACCURACY
200µA	0.01µA	±1.5% of rdg±5 digits
2000µA	1µA	
20mA	10µA	
200mA	100µA	
2A	1mA	
20A	10mA	±2.0% of rdg±10 digits

### RESISTANCE

RANGE	RESOLUTION	ACCURACY
200Ω	0.1Ω	±1.0% of rdg±3 digits
2kΩ	1Ω	
20kΩ	10Ω	
200kΩ	100Ω	
2MΩ	1kΩ	±1.5% of rdg±3 digits
200MΩ	10kΩ	

### TEMPERATURE

RANGE	RESOLUTION	ACCURACY
-40~1000°C	1°C	<400°C±(1.0% +5) digit ≥400°C±(1.5% +15) digit
0~1832°F	1°F	<750°F±(1.0% +5) digit ≥750°F±(1.5% +15) digit

### POWER : 9V (6F22) x 1

<b>Dimension</b>	: H170 x W86 x D35 mm
<b>Weight</b>	: Approx. 290 Gms.
<b>Accessories</b>	: Test leads, User Manual, TP04 Temperature Probe & Battery.
<b>Qty</b>	: 30 Pcs. in a Box.