



### FEATURES :

- 3<sup>1/2</sup> DIGIT MULTIMETER
- 5,999 COUNT
- AUTO RANGE
- AUTO POWER OFF
- MAX/MIN HOLD
- DUAL LCD WITH BARGRAPH
- LIVE TEST (SOUND AND LIGHT ALARM)
- NCV
- TRUE RMS
- DOUBLE COLOUR BACKLIGHT
- INPUT JACK LED INDICATOR

### DC VOLTAGE

RANGE	RESOLUTION	ACCURACY
600mV	0.1mV	±0.5% of rdg ±3 digits
6V	0.001V	
60V	0.01V	
600V	0.1V	
1000V	1V	

### DC CURRENT

RANGE	RESOLUTION	ACCURACY
600μA	0.1μA	±1.2% of rdg ±3 digits
6000μA	1μA	
60mA	0.01mA	
600mA	0.1mA	
10A	0.01A	

### FREQUENCY/DUTY

RANGE	RESOLUTION	ACCURACY
10Hz	0.001 Hz	±1.0% of rdg ±3 digits
100Hz	0.01Hz	
1000Hz	0.1Hz	
10kHz	0.001kHz	
100kHz	0.01kHz	
1000kHz	0.1kHz	
10MHz	0.001MHz	±3.0% of rdg ±3 digits
1~99%	0.1%	

### AC VOLTAGE

RANGE	RESOLUTION	ACCURACY
600mV	0.1mV	±0.8% of rdg ±5 digits
6V	0.001V	
60V	0.01V	
600V	0.1V	
750V	1V	

### AC CURRENT

RANGE	RESOLUTION	ACCURACY
600μA	0.1μA	±1.5% of rdg ±3 digits
6000μA	1μA	
60mA	0.01mA	
600mA	0.1mA	
10A	0.01A	

### TEMPERATURE

RANGE	RESOLUTION	ACCURACY
°C	1°C	-20°C~0°C ±5.0% rdg or ±3°C
		0°C~400°C ±1.0% rdg or ±2°C
		400°C~1000°C ±2.0% rdg
°F	1°F	-4°F~32°F ±5.0% rdg or ±6°F
		32°F~752°F ±1.0% rdg or ±4°F
		752°F~1832°F ±2.0% rdg

### RESISTANCE

RANGE	RESOLUTION	ACCURACY
600Ω	0.1Ω	±1.0% of rdg ±3 digits
6kΩ	0.001Ω	
60kΩ	0.01kΩ	
600kΩ	0.1kΩ	
6MΩ	0.001MΩ	±1.5% of rdg ±3 digits
60MΩ	0.01MΩ	

### CAPACITANCE

RANGE	RESOLUTION	ACCURACY
10nF	0.001nF	±4.0% of rdg ±5 digits
100nF	0.01nF	
1000nF	0.1nF	
10μF	0.001μF	
100μF	0.01μF	
1000μF	0.1μF	±5.0% of rdg ±5 digits
10mF	0.001mF	
100mF	0.01mF	

### POWER : AAA 1.5V x 2

<b>Dimension</b>	: H190 x W88 x D53 mm
<b>Weight</b>	: Approx. 290 Gms.
<b>Accessories</b>	: Test Leads, Sheath, TP04 Thermocouple, Manual & Battery .
<b>Qty</b>	: 40 Pcs. in a Box.