



FEATURES :

- 4½ DIGIT MULTIMETER
- 19,999 COUNT
- TRUE RMS
- DATA HOLD
- AUTO POWER OFF
- hFE TEST
- FUSE PROTECTION

DC VOLTAGE

RANGE	RESOLUTION	ACCURACY
200mV	10µV	±0.05% of rdg ±1 digits
2V	100µV	
20V	1mV	
200V	10mV	±0.1% of rdg ±5 digits
1000V	100mV	

FREQUENCY

RANGE	RESOLUTION	ACCURACY
20kHz	1Hz	±1.0% of rdg ±20 digits
200kHz	10Hz	

AC VOLTAGE

RANGE	RESOLUTION	ACCURACY	INPUT FREQUENCY
200mV	10µA	±0.8% of rdg ±80 digits	50Hz-20kHz
2V	100µA		
20V	1mV		
200V	10mV	±1.0% of rdg ±50 digits	50Hz-5kHz
750V	100mV		50Hz-400kHz

AC CURRENT

RANGE	RESOLUTION	ACCURACY	INPUT FREQUENCY
200mA	10µA	±0.8% of rdg ±80 digits	50Hz-5kHz
2A	100µA	±1.5% of rdg ±50 digits	50Hz-400kHz
20A	1mA		

DC CURRENT

RANGE	RESOLUTION	ACCURACY
20mA	1µA	±0.35% of rdg ±10 digits
200mA	10µA	
2A	100µA	±1.2% of rdg ±20 digits
20A	1mA	

CAPACITANCE

RANGE	RESOLUTION	ACCURACY
20nF	1pF	±3.5% of rdg ±20 digits
2µF	100pF	
200µF	10nF	±5.0% of rdg ±30 digits

RESISTANCE

RANGE	RESOLUTION	ACCURACY
200Ω	0.01Ω	±0.1% of rdg ±10 digits
2kΩ	0.1Ω	
20kΩ	1Ω	±0.1% of rdg ±5 digits
200kΩ	10Ω	
2MΩ	100Ω	
20MΩ	1kΩ	±0.6% of rdg ±5 digits

FREQUENCY

RANGE	RESOLUTION	ACCURACY
20kHz	1Hz	±1.0% of rdg ±20 digits
200kHz	10Hz	

TRANSISTOR hFE TEST

RANGE	RESOLUTION	ACCURACY
NPN or PNP	0~1000	Base current is approx 10µA Vce is approx 3V

POWER : DC 220V

Dimension	: H260 x W220 x D82 mm
Weight	: Approx. 2Kgs.
Accessories	: Test Leads, Sheath, Power Cord & Manual
Qty	: 6 Pcs. in a Box.