

DIGITAL AC CLAMP METER

CM-2007



AC / DC Voltage	NCV
AC Current	Frequency
Torch	Resistance
Diode	Capacitance
Temp	Continuity
Back light	Over Range Display
Low Battery Indication	600V

FEATURES :

- 3 3/4 DIGIT
- 3,999 COUNT
- JAW OPEN : 28 MM, WITH LIGHTING
- AUTO POWER OFF (APO)
- TRUE RMS
- DATA HOLD

DC VOLTAGE

RANGE	RESOLUTION	ACCURACY
400mV	0.1mV	±1.0% of rdg ±5 digits
4V	1mV	±0.5% of rdg ±5 digits
40V	10mV	
400V	100mV	
600V	1V	

AC VOLTAGE

RANGE	RESOLUTION	ACCURACY
4V	1mV	±1.0% of rdg ±5 digits
40V	10mV	
400V	100mV	
600V	1V	

CAPACITANCE

RANGE	RESOLUTION	ACCURACY
4nF	1pF	±5.0% of rdg ±10 digits
40nF	10pF	
400nF	100pF	±2.5% of rdg ±5 digits
4μF	1nF	
40μF	10nF	
400μF	100nF	
4mF	1μF	±5.0% of rdg ±10 digits
40mF	10μF	

AC CURRENT

RANGE	RESOLUTION	ACCURACY
4A	1mA	±3.0% of rdg ±5 digits
40A	10mA	
400A	100mA	±2.0% of rdg ±5 digits
800A	1A	

RESISTANCE

RANGE	RESOLUTION	ACCURACY
400Ω	0.1Ω	±0.8% of rdg ±5 digits
4kΩ	1Ω	±0.8% of rdg ±3 digits
40kΩ	10Ω	
400kΩ	100Ω	
4MΩ	1kΩ	
40MΩ	10kΩ	±1.0% of rdg ±5 digits

POWER : 1.5V AAA x 2

Dimension	: H185 x W65 x D32 mm
Weight	: Approx. 200 g.
Accessories	: Test leads, User Manual, TP04 Thermocouple, Carrying Bag & Battery.
Qty	: 40 Pcs. in a Box.

FREQUENCY/DUTY

RANGE	RESOLUTION	ACCURACY
10Hz	0.01 Hz	±0.5% of rdg ±4 digits
100Hz	0.1Hz	
1kHz	1Hz	
10kHz	10Hz	
100kHz	100Hz	
1MHz	1kHz	
10MHz	10kHz	

TEMPERATURE

RANGE	RESOLUTION	ACCURACY
-40~1000°C	1°C	<400°C ±(1.0% +5) digit ≥400°C ±(1.5% +15) digit
0~1832°F	1°F	<750°F ±(1.0% +5) digit ≥750°F ±(1.5% +15) digit