



AC / DC Voltage	NCV
AC Current	Diode
Torch	Resistance
Back light	Continuity
Temp	Over Range Display
Low Battery Indication	600V

FEATURES :

- 3½ DIGIT
- 1,999 COUNT
- JAW OPEN : 52 MM
- TRUE RMS
- DATA HOLD
- FUNCTION PROTECTION
- AUTO POWER OFF

DC VOLTAGE

RANGE	RESOLUTION	ACCURACY
200mV	0.1mV	±0.5% of rdg ±5 digits
20V	10mV	
1000V	1V	±1.0% of rdg ±5 digits

AC CURRENT

RANGE	RESOLUTION	ACCURACY
200A	0.1A	±2.0% of rdg ±5 digits
1000A	1A	

AC VOLTAGE

RANGE	RESOLUTION	ACCURACY
20V	10mV	±1.0% of rdg ±5 digits
750V	1V	±1.2% of rdg ±5 digits

RESISTANCE

RANGE	RESOLUTION	ACCURACY
200Ω	0.1Ω	±0.8% of rdg ±5 digits
2kΩ	1Ω	
20kΩ	10Ω	±0.8% of rdg ±1 digits
200kΩ	100Ω	
2MΩ	1kΩ	±1.2% of rdg ±5 digits
20MΩ	10kΩ	
200MΩ	100kΩ	

TEMPERATURE

RANGE	RESOLUTION	ACCURACY
-40°C~1000°C	1°C	<400°C ±(1.0% +5) digit ≥400°C ±(1.5% +15) digit
0°F~1832°F	1°F	<750°F ±(1.0% +5) digit ≥750°F ±(1.5% +15) digit

POWER : 1.5V AAA x 2

Dimension	: H270 x W123 x D35 mm
Weight	: Approx. 280 g.
Accessories	: Test leads, Manual, Carrying Bag & Battery.
Qty	: 30 Pcs. in a Box.