



- AC / DC Voltage
- AC / DC Current
- Torch
- Diode
- Back light
- Temp
- Low Battery Indication
- NCV
- Resistance
- Capacitance
- Continuity
- Over Range Display
- CAT III 600V**

FEATURES :

- 3½ DIGIT
- 1,999 COUNT
- JAW OPEN : 52 MM
- AUTO POWER OFF (APO)
- TRUE RMS
- MAX / MIN / RELATIVE
- DATA HOLD
- AUTO / MANUAL RANGE

DC VOLTAGE

RANGE	RESOLUTION	ACCURACY
200mV	0.1mV	±1.0% of rdg ±5 digits
2V	1mV	±0.5% of rdg ±5 digits
20V	10mV	
200V	100mV	
1000V	1V	±1.0% of rdg ±5 digits

DC CURRENT

RANGE	RESOLUTION	ACCURACY
200V	100mA	±2.0% of rdg±5 digits
1000V	1A	

CAPACITANCE

RANGE	RESOLUTION	ACCURACY
400µF	100mF	±5.0% of rdg±10 digits
4mF	1µF	
40mF	10µF	

AC VOLTAGE

RANGE	RESOLUTION	ACCURACY
200mV	0.1mV	±1.5% of rdg ±5 digits
2V	1mV	±1.0% of rdg ±5 digits
20V	10mV	
200V	100mV	
750V	1V	±1.5% of rdg ±5 digits

AC CURRENT

RANGE	RESOLUTION	ACCURACY
200V	100mA	±2.0% of rdg±5 digits
1000V	1A	

RESISTANCE

RANGE	RESOLUTION	ACCURACY
200Ω	0.1Ω	±0.8% of rdg±5 digits
2kΩ	1Ω	±0.8% of rdg±3 digits
20kΩ	10Ω	
200kΩ	100Ω	
2MΩ	1kΩ	
20MΩ	10kΩ	±1.2% of rdg±5 digits

POWER : 1.5V AAA x 2

Dimension	: H185 x W65 x D32 mm
Weight	: Approx. 200 g.
Accessories	: Test leads, Manual, TP04 Thermocouple, Carrying Bag & Battery.
Qty	: 30 Pcs. in a Box.