

**CE-8200/CE8202/CE-8203**



**Features:**

- 4 Digit LCD Display with Black Screen
- 9,999 Count
- Auto Power Off (APO)
- Conductor Size: 55mm x 32mm
- Data Logging System 300 groups memory
- Measure 2 times / sec.
- Double Insulation Protection Level
- Spare 1 & 10 Test Ring, to detect Self Precision

MODEL	RESISTANCE RANGE	CURRENT RANGE
CE-8200	0-1000Ω	NA
CE-8202	0-1200Ω	0.00mA-20A
CE-8203	0-200Ω	NA

**RESISTANCE**

Range	Resolution	Accuracy
0.010~0.099Ω	0.001Ω	±1% of rdg + 0.1Ω digits
0.10~0.99Ω	0.01Ω	
1.0~49.9Ω	0.1Ω	
50.0~99.5Ω	0.50Ω	±1.5% of rdg + 0.5Ω digits
100~199Ω	1Ω	±2% of rdg + 1Ω digits
200~395Ω	5Ω	±5% of rdg + 5Ω digits
400~590Ω	10Ω	±10% of rdg + 10Ω digits
600~1000Ω	20Ω	±20% of rdg + 20Ω digits
*900~1200Ω	30Ω	± (25% + 30Ω)

\*For CE - 8202

**CURRENT** (For CE - 8202)

Range	Resolution	Accuracy
0.00mA - 9.95mA	0.1mA	±(2.5% + 1mA)
10.0mA - 99.0mA	0.1mA	±(2.5% + 5mA)
100mA - 300mA	1mA	±(2.5% + 10mA)
0.30A-2.99A	0.01A	±(2.5% + 0.1A)
3.0A-9.9A	0.1A	±(2.5% + 0.3A)
10.0A-20.0A	0.1A	±(2.5% + 0.5A)

**POWER**

AA 1.5V X 4

- Standard Accessories : Hard Carrying Case, Test Loop, Manual
- Dimension : 285(H) x 85(W) x 58(D)mm

