

TECHNICAL DATA

Fluke 15B+ Digital Multimeter



Key features

- 600 V Cat III safety rating
- AC/DC voltage measurement up to 1000V
- AC/DC current measurement up to 10A
- Measures voltage, resistance, continuity, capacitance
- Diode test, data hold
- Large easy-to-read display with bright white backlight

Product overview: Fluke 15B+ Digital Multimeter

Fluke quality is always within your reach

Unlock professional-grade precision, durability, and safety with the Fluke 15B+ Digital Multimeter. The Fluke 15B+ packs all the core functionality you need in a digital multimeter into a portable, rugged form tool that's easy-to-use with one hand, even with gloves on. From AC/DC voltage and current measurements up to 1000V and 10A, to comprehensive capabilities including resistance, capacitance, and frequency checks, the 15B+ is your go-to for troubleshooting a wide array of electrical issues.

The CAT III 600V safety rating provides peace of mind for everything from routine checks on electrical equipment and appliances, to checking voltage levels at power outlets or switches, to diagnosing issues with circuits. Ideal for both DIY enthusiasts and early career electricians looking to streamline their toolkit, the Fluke 15B+ is a reliable and versatile addition to your toolkit.

Specifications: Fluke 15B+ Digital Multimeter

Accuracy Specifications

Accuracy is specified for 1 year after calibration, at operating temperatures of 18 u00b0C to 28 u00b0C, relative humidity at 0% to 75%. Accuracy specifications take the form of: u00b1(% of Reading + Number of Least Significant Digits).

Function	Range	Resolution	Accuracy	
AC volts (40 Hz to 500Hz) ¹	4.000 V 40.00 V 400.0 V 1000 V	0.001 V 0.01 V 0.1 V 1 V	1.0% + 3	
DC volts	4.000 V 40.00 V 400.0 V 1000 V	0.001 V 0.01 V 0.1 V 1 V	0.5% + 3	
AC millivolts	400.0 mV	0.1 mV	3.0% + 3	
DC millivolts	400.0 mV	0.1 mV	1.0% + 10	
Diode test ²	2.000 V	0.001 V	10%	

Resistance (Ohms)	400.0 u03a9 4.000 ku03a9 40.00 ku03a9 400.0 ku03a9 4.000 Mu03a9 40.00 Mu03a9	0.1 u03a9 0.001 ku03a9 0.01 ku03a9 0.1 ku03a9 0.001 Mu03a9 0.01 Mu03a9	0.5% + 3 0.5% + 2 0.5% + 2 0.5% + 2 0.5% + 2 1.5% + 3	
Capacitance ³	40.00 nF 400.0 nF 4.000 u03bcF 40.00 u03bcF 400.0 u03bcF 1000 u03bcF	0.01 nF 0.1 nF 0.001 u03bcF 0.01 u03bcF 0.1 u03bcF 1 u03bcF	2% + 5 2% + 5 5% + 5 5% + 5 5% + 5 5% + 5	
AC current u03bcA (40 Hz to 400 Hz)	400.0 u03bcA 4000 u03bcA	0.1 u03bcA 1 u03bcA	1.5% + 3	
AC current mA (40 Hz to 400 Hz)	40.00 mA 400.0 mA	0.01 mA 0.1 mA	1.5% + 3	
AC current A (40 Hz to 400 Hz)	4.000 A 10.00 A	0.001 A 0.01 A	1.5% + 3	
DC current u03bcA	400.0 u03bcA 4000 u03bcA	0.1 u03bcA 1 u03bcA	1.5% + 3	
DC current mA	40.00 mA 400.0 mA	0.01 mA 0.1 mA	1.5% + 3	
DC current A	4.000 A 10.00 A	0.001 A 0.01 A	1.5% + 3	
Backlight	Yes			

¹AC volts are specified from 1% to 100% of range. Inputs below 1% of range are not specified.

²Typically, open circuit test voltage is 2.0 V and short circuit current is <0.6 mA.

³Specifications do not include errors due to test lead capacitance and capacitance floor (may be up to 1.5 nF in the 40 nF range).

Function	Overload protection	Input impedance (Nominal)	Common mode rejection ratio	Normal mode rejection ratio
AC volts	1000 V ¹	>10 Mu03a9 <100 pF	>60 dB at dc, 50 Hz or 60 Hz	-
AC millivolts	400 mV	>1Mu03a9, <100 pF	>80 dB at 50 Hz or 60 Hz	-
DC volts	1000 V ¹	>10 Mu03a9 <100 pF	>100 dB at dc, 50 Hz or 60 Hz	>60 dB at 50 Hz or 60 Hz
DC millivolts	400 mV	>1Mu03a9, <100 pF	>80 dB at 50 Hz or 60 Hz	-

¹ 10⁶ V Hz Max

General specifications

Maximum voltage between any terminal and earth ground	1000 V
Display (LCD)	4000 counts, updates 3/sec
Baery type	2 AA, NEDA 15A, IEC LR6
Baery life	500 hours minimum
Temperature	

Operating	0 u00b0C to 40 u00b0C
Storage	-30 u00b0C to 60 u00b0C
Relative humidity	
Operating humidity	Non-condensing (<10u00b0C) u226490% RH at 10 u00b0C to 30 u00b0C; u226475% RH at 30 u00b0C to 40 u00b0C
	40 Mu03a9 range u226480% RH at 10 u00b0C to 30 u00b0C; u226470% RH at 30 u00b0C to 40 u00b0C
Altitude	
Operating	2000 m
Storage	12,000 m
Temperature coefficient	0.1 X (specified accuracy) /u00b0C (<18 u00b0C or >28 u00b0C)
Fuse protection for current inputs	440 mA, 1000 V Fast Fuse, Fluke specified part only. 11A, 1000V Fast Fuse, Fluke specified part only.
Size (H x W x L)	183 x 91 x 49.5 mm
Weight	455 g
IP rating	IP 40
Safety	IEC 61010-1, IEC61010-2-030 CAT III 600 V, Pollution Degree 2
Electromagnetic Compatibility	IEC 61326-1: Portable EMC Environment
Class A equipment (industrial broadcasting & communication equipment) ¹ ¹ This product meets requirements for industrial (Class A) electromagnetic wave equipment and seller or user should take notice of it. This equipment is intended for use in business environments and is not to be used in homes.	

Ordering information



Fluke 15B+

Fluke 15B+ Digital Multimeter

Includes:

- TL75 test leads with two caps
 - 2 AA batteries
 - User's manual
-



Fluke. *Keeping your world up and running.®*

Fluke Corporation
PO Box 9090, Everett, WA 98206 U.S.A.

For more information call:
In the U.S.A. (800) 443-5853
In Canada (800) 36-FLUKE
From other countries +1 (425) 446-5500
www.fluke.com

©2024 Fluke Corporation.
Specifications subject to change without notice.
11/2024

**Modification of this document is not permitted
without written permission from Fluke Corporation.**