

TECHNICAL DATA

Fluke 931 Contact and Non-Contact Dual-Purpose Tachometers









Key features

- 6-digit backlight display reads the data clearly
- Signal detection reminder avoids invalid detection actions
- Maximum/minimum/average value and final readings
- Setting/Turning off the automatic power-off function
- Small size and easy to hold
- Easy switching of the contact and non-contact measurement modes
- Different speed measuring heads and rotational speeds adapt to different measurement occasions
- 1-year warranty

Product overview: Fluke 931 Contact and Non-Contact Dual-Purpose Tachometers

The Fluke 931 tachometer is a handheld tachometer, which integrates the contact and non-contact speed measurement functions and can accurately measure the revolutions per minute (RPM) or surface speed and distance. Fluke 930 is equivalent to a Fluke 931 with minimum configuration. With only the non-contact measuring function provided, it's more affordable and offers consistent quality.

Applications:

- · Heavy manufacturing environments, e.g. automotive, textile, pulp and paper, metalwork
- Water purification plants
- Machining and chemical manufacturing plants
- HVAC compressors for industrial systems

Specifications: Fluke 931 Contact and Non-Contact Dual-Purpose Tachometers

| Rotation speed measurement | | |
|----------------------------|--|--|
| Range | Optical (non-contact) measurement: 1 to 99999 revolutions/minute ttContact measurement: 1 to 19999 revolutions/minute (Fluke 931 only) | |
| Precision | u00b10.02% RD+1 | |
| Sensing distance | (optical) 500 mm | |



| Specifications | | |
|-----------------------|----------------------------------|--|
| Baery type | (2) 1.5V LR6 (alkaline) AA baery | |
| Baery life | About 40 hours | |
| Operating temperature | 0u00b0C to 50u00b0C | |
| Storage temperature | -20u00b0C to 70u00b0C | |
| Weight | 250 g | |
| Dimensions | 175 u00d7 60 u00d7 28 mm | |
| Warranty period | 1 year | |



Ordering information



Fluke 931

Fluke 931 Contact and Non-Contact Dual-Purpose Tachometers

- 0.1 m wheel
- Conical speed measuring head
- Inner cone speed measuring head
- Lengthening rod
- 10 reflective stripes



Fluke. Keeping your world up and running.®

Fluke Corporation

PO Box 9090, Everett, WA 98206 U.S.A.

For more information call: In the U.S.A (800) 443-5853

In Canada (800) 36-FLUKE From other countries +1 (425) 446-5500

www.fluke.com

©2024 Fluke Corporation.

Specifications subject to change without notice. 11/2024

Modification of this document is not permitted without written permission from Fluke Corporation.