



## PRO TTRS-1 TRANSFORMER TURNS RATIO TESTER

### PRODUCT INTRODUCTION

The Metravi TTRS-1 Transformer Turns Ratio Tester adopts microprocessor technology for measurement calculation and automatic control, which can quickly and easily measure the actual transformer ratio and group of the transformer.

It is mainly used for measuring transformer turns ratio and group in the power industry, and it is also used for measuring transformer parameters by transformer manufacturers and distributors.

The Metravi TTRS-1 Transformer Turns Ratio Tester is composed of the main machine, monitoring software, test line, communication line, etc. The host has the charging function without the need to find electricity.

It comes with a full colour large screen LCD display, at a glance touchscreen operation, easy to use, port anti-overload function, large capacity storage of 500 sets of data. The upper computer software has the functions of reading, consulting and saving historical data.

### FEATURES

- Various test modes: single-phase test, three-phase test, three-phase blind test, Z-type test
- Large capacity storage: It can store 500 sets of test data
- Wide measurement range: variable ratio 0.9~10000
- Measurement accuracy: 0.2% when the variable ratio is 0.9 to 2000, and 0.5% from 2000 to 10000
- Max. resolution: 0.0001
- Support for computer-side control
- Support for Bluetooth control



\*Images and Specifications are subject to change without prior notice

## PRO TTRS-1 TRANSFORMER TURNS RATIO TESTER

### TECHNICAL SPECIFICATIONS

<b>Function</b>	It is mainly used for transformer ratio and group test of three-phase transformer, transformer ratio and polarity test of single-phase transformer, PT and CT. This product can conduct blind test of three-phase transformer and change ratio and group test of Z-type transformer.
<b>Type of test product</b>	Single-phase transformer, three-phase transformer, Z-type transformer, PT, CT
<b>Variable ratio range</b>	0.9~10000
<b>Overload protection</b>	Yes
<b>Power</b>	DC9.6V 3800mAh Large capacity lithium battery
<b>Charging function</b>	Yes
<b>Display mode</b>	5-inch touchscreen (854dots 480dots) full-colour LCD display
<b>Interactive mode</b>	Touch screen / button
<b>LCD size</b>	Length /width: 108 mm×65mm
<b>Instrument size</b>	length, width and height: 229mm×166mm×74mm
<b>Mobile APP</b>	Yes, Bluetooth connection
<b>Computer connect</b>	Yes, the USB cable connection
<b>Data storage</b>	500sets
<b>Data access</b>	Data access function
<b>Battery voltage</b>	Real-time display of battery power indicates that the battery should be charged in time when the voltage is low
<b>Auto shut off</b>	Automatic shutdown can be set for 1 to 30 minutes

## PRO TTRS-1 TRANSFORMER TURNS RATIO TESTER

### TECHNICAL SPECIFICATIONS

Power dissipation	Standby: about 2W (100% brightness)
	Measured at: 12W Max
Weight	Instrument: 1.5kg (including battery)
	Test cables: 1.7kg
Working temperature and humidity	-10°C~40°C; below 70%RH
Store temperature and humidity	-20°C~60°C; below 70%RH
Insulation resistance	Above 10 MΩ (500V between circuit and housing)
Withstand voltage	AC 3700V / rms (between circuit and enclosure)
Electromagnetic characteristics	IEC61010-4-3, Wireless frequency electromagnetic field≤1V/m
Suitable for safety regulations	IEC61010-1、CAT III 600V、Pollution grade 2

### ACCESSORIES

- Test Cables
- Software CD
- USB Cable
- User Manual
- Carrying Case
- Charger



\*Images and Specifications are subject to change without prior notice